

Safety

The Linde T16L benefits from a long tiller with a low mounting point ensuring a large safety clearance between operator and chassis. While using optional buttons or automatic function from the chassis side, the lowering stops automatically to keep the operator's feet safe. Creep speed and proportional speed functions, available as options, provide optimum safety while travelling or manoeuvring in tight corners.

Performance

The T16L shows its true efficiency on the job. The powerful lift and traction motors supply the performance needed to achieve a high level of productivity. Wide spaced mast channels provide excellent stability for the load enabling a residual capacity of 800 kg in fully raised position.

Comfort

Empty pallets can be raised by 804 mm, eliminating back or upper body strain. This height adjustment is really appreciated when order picking, restocking shelves in retail stores or assembly line activities in manufacturing industries. Additional buttons located on the truck side and automatic functions enable all kind of loads to be lifted or lowered quickly and without fatigue.



Reliability

A rugged construction makes the T16L a pallet truck that can be relied on. The Extraal® motor cover is remarkably solid and resistant to damage. The sturdy mast and the durable carriage are made of high-grade rolled steel contributing to a long truck life as well as fast, easy and safe load handling.

Service

Linde pallet trucks are designed to keep maintenance costs low and provide high levels of up-time over many years. The service engineer has fast, easy access to all internal components thus enabling a quick maintenance turnaround.